

Duct Hoses

Pneumics duct hoses are reinforced with a continuous rigid material helix. smooth bore provides minimum frictional resistance. Pneumics duct hoses are recommended for light bulk material handling, dust control, air movement and fume control applications. These lightweight and flexible hoses provide good chemical resistance and are ideal for areas where flexibility and tight bending characteristics are a must.



Characteristics

- Lightweight and flexible.
- Good chemical resistance.
- Popular choice for general industrial vacuum applications.
- Recommended Maximum Working Temperature 60/65 °C.

Duct Hose - Grey Colour

Code	Normal Bore		Diameter		Wall Thickness mm	Pressure (AT 30 C)		Standard Length (Mtrs)
	Inch	mm	ID (mm)	OD (mm)		W. P. (bar)	B. P. (bar)	
DH-25-30	1"	25	25.40±0.5	31.10±1.5	3.5	3.75	16.0	30
DH-32-30	1-1/4"	32	31.18±0.5	40.00±0.5	4.0	3.10	10.75	30
DH-38-30	1-1/2"	38	38.00±1.0	45.00±1.0	4.0	3.10	10.75	30
DH-50-30	2"	50	50.80±1.0	57.20±1.0	4.0	2.60	8.20	30
DH-63-30	2-1/2"	65	60.50±1.5	68.50±1.5	4.5	1.50	6.00	30
DH-75-30	3"	75	76.50±1.5	83.54±1.5	4.5	1.40	5.50	30
DH-90-30	3-1/2"	90	89.00±1.5	97.60±1.5	4.5	0.60	3.40	30
DH-100-15	4"	100	101.20±1.5	108.94±1.5	4.5	0.90	4.20	15
DH-100-30	4"	100	101.20±1.5	108.94±1.5	4.5	0.90	4.20	30
DH-125-15	5"	125	127.00±2.0	135.20±2.0	4.5	0.60	3.40	15
DH-150-15	6"	150	152.40±2.0	161.10±2.0	4.5	0.60	2.80	15
DH-200-15	8"	200	204.00±2.0	214.40±2.0	5.0	0.45	2.10	15
DH-250-10	10"	250	253.00±2.0	264.00±2.0	6.0	0.30	2.00	10
DH-300-10	12"	300	305.00±2.0	319.00±2.0	7.0	0.25	2.00	10